CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

MODEL L-67 PORTABLE LOAD BANK

THE L-67 LOAD BANK is designed to provide a temporary load for field servicing and testing 120/240 volt single phase or 120/208 three phase 60HZ generators and inverters. This load bank is air cooled and completely self contained. The unit can load three phase 208VAC up to 70KW and 240VAC single phase up to 46KW. The unit can also load

MODEL L-67 DIMENSIONS

Length	22"
Width	8"
Height	21"
Weight	



FEATURES

- Load steps: 1,2,2, 5, 10, 20, 30KW @208VAC Three Phase
- Load steps: .66,1.32,1.32, 3.3, 6.6, 13.3, 19.8KW @240VAC single phase
- Load steps: .33,.66,.66, 1.7, 3.3, 6.6, 9.9KW @120VAC single phase
- Plug test pins for connecting test leads
- Receptacle for ten foot cable(included with load bank)
- Meters: 0-150VDC voltmeter, 0-200A ammeter, 55-65HZ frequency meter
- **Power indicator lights**
- **Thermal protection**
- **Carrying case**
- **Folding handle**

WEBSITE: WWW.CANNONLOADBANKS.COM